Lantechi

It's a Lantech!

Work smarter. . . Keep your driver on the fork truck!

- All of the features and benefits of our popular Q-400 with automation added:
 - (1) Patented XT Cut and Clamp® automatically captures the stretch film and cuts it at the end of the wrap cycle.
 - (2) Save two minutes of fork truck driver labor per load.
- No scheduled preventative maintenance.



More Lantech field-tested packaging solutions @ www.lantech.com

Q-400XT

Rev. 06/07/12

Simple Automation™ Stretch

Lantech

Wrapping System

Page 1 of 2

Q-400XT

Eliminate the "run-around" with Simple Automation™ in a fast - paced environment.

Q-400XT automatically attaches and cuts the film. Equipped with a fully protected mechanical cut & clamp. Improve productivity by keeping the operator on the fork truck.

Q-400XT Specifications

PERFORMANCE CRITERIA

- Production Speed
- Maximum Load Diagonal
- Maximum Load Height
- Maximum Load Weight

LOAD HANDLING SYSTEM

- Turntable Drive ■ Turntable Speed
- Turntable, Smooth Top

FILM DELIVERY SYSTEM

- Power-Roller Stretch Plus System
- Wrapping Force
- Pallet Grip
- Film Capacity

250% Standard (100%-300% available)

Electronically controlled 10" Roll Diameter, 20" Film Web Width

30-40 loads per hour

69" Recommended

1 HP TEFC Motor

5000 lbs.

1-12 RPM

Standard

MACHINE SHIPPING WEIGHT

- Machine size
- Shipping Weight (including skid approximate)

119"L x 67"W x 92"H (excludes ramp)

ELECTRICAL REQUIREMENTS

- Machine Voltage
- Microcontroller
- Wrap Cycle Pause
- NEMA 12 Enclosure

SERVICE SUPPORT

120V, 20 Amp Standard Standard Standard

24 hrs/7 days a week PHONE NUMBER 800-866-0322

Specifications subject to change without notice. Lantech systems and sub-systems are protected by U.S. and foreign patents. Additional U.S. and foreign patents pending. © Lantech

Boost your machine's performance with these features: **EZ Weigh™Integrated Scale**

Check Every Load for Quality and Freight Cost!

Weigh and wrap in one easy step.

Patented built-in weigh system is fully integrated into the turntable.



Same footprint as standard Q semi-automatic.

Click-n-Go


Stretch Wrapping Loads at the Touch of a Button!

Enhances portability by eliminating requirement to install a ceilingmounted lanyard.

Each unit can handle up to 3 machines.



Click-n-Go remote meets the latest safety requirements outlined by the National Electrical Code. Using infrared technology and two-step activation process, the Click-n-Go is immune to accidental activation from stray radio frequency.



MEMBER PMMI USA