

Introducing Load Guardian 2.3.1, featuring READY TO WRAP PROFILES

Operators simply match one of the prebuilt, Ready to Wrap Profiles to their load and push start, eliminating the guess work for stretch wrapping almost any load configuration.

Additional New Features

- Expanded capabilities for:
 - Short Loads
 - Reverse Rotation
 - Wrap Heights

The screenshot displays the mobile application interface for Load Guardian 2.3.1. At the top, it shows the user role as 'ADMINISTRATOR', the date and time '2/24/21 3:23 PM', and a 'MENU' icon. Below this is a header with 'NAME', 'SELECT A PROFILE', and 'DETAIL'. The main content area is a grid of 10 profile cards, each with a title, description, and a small diagram of the load configuration. The profiles are:

- Regular Light**: Light Load with no sharp edges. Applies Light Film Tension.
- Regular Heavy**: Heavy and fits the pallet with no sharp edges. Applies Light Film Tension.
- Irregular Light**: Very light product that does not fit squarely on the pallet. Applies Light Film Tension.
- Irregular Heavy**: Heavy and irregular load. Applies Light Film Tension.
- Sharp Edges**: Load has very sharp edges and is extremely inboard. Applies Moderate Film Tension.
- Incomplete Top Layer**: A load that has a few extra boxes on top. Requires Hand-Roping. 4 revolutions at slow turntable speed.
- Soft Top**: Very soft or light top layer. Film tension is reduced at the top.
- Pre-wrapped Double Load**: Stacked loads have already been wrapped. Applies 3 layers to the middle.
- Short Normal**: Short load that does not require roping. Applies Light Film Tension.
- Very Short and Inboard**: Very short load that is extremely inboard. (Incompatible with XT). Requires Hand-Roping. 4 revolutions at slow turntable speed.

At the bottom of the screen, there are three buttons: 'CREATE NEW PROFILE', 'LEGACY CONTROLS', and 'INITIALIZE'.

Lantech®

Introducing the NEW QL-400 Semi-Automatic Stretch Wrapper



PROTECTED BY
Load Guardian
*Creates, Maintains & Delivers
Safe-to-Ship Loads*




QL-400

Load Guardian is Lantech's patented control system that *creates, maintains* and *delivers* the right containment force for safe-to-ship loads every time. It minimizes operator interaction and eliminates the guess work for stretch wrapping any load configuration.




Intelligent Set-up



Intuitively guides users through the profile creation process, using recognizable icons and smartphone-like simplicity, to calculate the right containment force.




Wrap Apps



Eliminates the need for operators to make machine adjustments for common load applications (e.g. stack & band, stack & wrap, labels, corner boards, top sheet, top box, short loads) through pre-established, yet customizable wrap profile settings.



Help



Provides simple video and text instruction for countering stretch wrapping problems: film breaks, product crushing, loads twisting, and more.




Robustness

Hundreds of machine improvements based on 25 years of Q machine warranty experience. Wire connections, motors, reducers, and sensors are improved. Plus new controls.



Production Reports

Advanced diagnostics, productivity charts and fault tracking.



Specifications

Performance	
Peak Production Speed	Up to 25-35 loads/hr
Turntable Speed (Variable)	12 RPM
Turntable Drive	1 HP TEFC
Load Handling	
Turntable Size	1.650 mm 65" Diameter
Maximum Load Diagonal / Dimensions	1.830 mm (72")
Maximum Load Height	70 mm (2 3/4")
Maximum Load Weight	2.268 kg (5000 lbs.)
Film Delivery System	
Film Delivery System	Power Roller-Stretch PLUS
Standard Pre-Stretch	250%
E-Z Thread Roll Carriage	Standard
Wrapping Force	Variable (Electric)
Film Capacity	250 mm Diameter (10" Diameter - 20" Length)
Standard Film Width	500 mm Width Optional (30" Width Opt)
Laser Height Sensor	Standard
Auto Film Cut-off	Standard
Pallet Grip®	Standard
Service Requirements	
Electric	120 Volt 20Amp-
Pneumatic	N/A
NEMA Type 1 Enclosure	Standard
Wrap Cycle Pause	Standard
One Way Wrap	Standard
Service Support	24 Hrs/7 Days a week
Phone Number	(800) 866-0322
Warranty	5 years, unlimited cycles

QL-400 Standard Performance Package

- **Pallet Grip®**
Keeps your loads from sliding off pallets during shipment.
- **Auto Film Cut-off™**
Saves 30 seconds of operator labor per load.
- **Power Roller Stretch Plus™**
Maximizes film delivery system performance.
- **NEMA Type 1 Enclosure**
Protects control system electronics from dust, dirt or moisture.
- **2.268KG (5,000 LBS) Weight Capacity and 1 HP Turntable Drive Motor.**
- **No Scheduled Preventative Maintenance.**

Options

EZ Weigh® Integrated Scale

Weigh and Wrap in One Easy Step!



Upgrade

UPGRADE to a QL-400XT

*Increase Productivity.
Keep Your Driver on the Forklift!*

