Lantech

Brick and Block

Brick and Block Packaging

Productivity

Providing creative solutions to help customer increase productivity.



Package Benefits

- Moisture Barrier
- Decorative Brick Protection
- Safer for Elevated Storage
- Better Containment


Automatic Stretch Wrapping



Brick and Block



Protective moisture barrier (polyethylene sheet) automatically applied to top of load during the wrapping cycle. Top sheet securely held on load with spiral wrapping.



At end of wrapping cycle, the film tail is secured with Lantech's patented film sealer. No unraveling of film during handling and shipping cycle.



Lantech-design heavy duty conveyor system handles the heaviest brick and block loads - up to 6000 lbs. Three year warranty, unlimited cycles.



Film roping option. Film web is automatically collapsed into a high strength "rope" for even more containment.

Specifications		
Performance	Q Series Solution	S Series Solution
Production Speed (based on 60" load height; 2 film layers and 10 revolutions)	Up to 45 loads per hour	75-90 loads per hour
Maximum Load Size	48"W x 54"L x 92"H	58"W x 58"L x 80"H
Maximum Load Weight	4000 lbs.	Conveyor Capacity
Load Handling		
Turntable Speed	1-12 RPM	1-40 RPM (depending on speed package)
Turntable Drive	1 HP TEFC	N/A
Film Delivery System		
Power Roller-Stretch® System	200% Standard, 100-300% Available	250% Standard, 100-300% Available
Wrapping Force	Electronic Control	Electronic Control
Film Capacity	10" Roll Diameter, 20" Film Web Width	10"Diameter, 20" Width

Specifications subject to change without notice.

